

CBU-GATEWAY

Vadsbo's CBU Gateway device enables remote access for up to four Casambi networks using the Gateway and Sites functionality in the Casambi app.

Remote connection via LAN, WIFI or 3G/4G with the addition of a pre-formatted data enabled sim card.

The CBU-Gateway can be used for remote diagnostics, network monitoring or remote control of up to 2 Casambi networks.

Provides automatic time backup for connected Networks in the event of a power outage.

Product Features:

Qualcomm MSM8909 Quad Core CPU
ARM Cortex-A7 microprocessor cores up to 1.1 GHz
QDSP6 v5 core at up to 691 MHz
2GB DDR3 memory
8GB EMMC
BT 4.1 (BR/EDR + BLE) Range up to 30M*
Size 108x104x28mm
Net Weight 180g
Operating Temperature 0° to 50° C
Operating Relative Humidity 10% to 95%
WiFi IEEE 802.11 b/g/n, 2.4G
LAN RJ45 10/100M Ethernet interface
HDMI Video output V1.4
3G/4G
UK Power Adapter AC 100 ~ 240V 50/60Hz
Control 2 Casambi networks

* We recommend the CBU-GATEWAY be placed within range of at least two nodes on each Casambi network to be controlled. Maximum range is based on ideal conditions.



CASAMBI